



A 1 temperature cabinet adjustable from 9 to 15° to mature your wines in the best possible conditions.



**EAN Code : 3543290002738**

CONFIGURATION	Storage shelves	Sliding shelves	Capacity**
Maximum Configuration (100% sliding)	-	13	170
Mixed Configuration	2	4	206
Minimum Configuration (100% storage)	4	0	230
<b>Standard Configuration</b>	<b>4</b>	<b>0</b>	<b>230</b>

## UNIVERSAL SHELF

### Universal shelf : AOHUI

**Weight:** 2.6 kg

**Type of structure:** slats

**Number of bottles per level :** 12

**Material:** Solid Beechwood coated with an ecological water varnish.

AOHUI shelf is universal. It can be positioned in



« Storage »  
72 Bottles



« Sliding »  
12 Bottles



« Presentation »  
6 + 36 Bottles

Artevino AOHUI shelf has a label holder :



Range :	<b>OXYGEN</b>
Model :	<b>OXGIT230NPD</b>
Fonction :	<b>Ageing</b>
Capacity* :	<b>230 Bottles**</b>



A constant temperature due to the dual Heating/Cooling controls.



Optimised humidity due to the circulation of humid air.



Air circulation ensured by the principle of thermodynamic pump.



No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.



Protection from UV light guaranteed with a solid door with highly effective UV filter.



« Storage and/or sliding » universal shelf. One shelf for all types of storages. Suitable to store all types of bottles.

GENERAL FEATURES	
Gross weight, packaged(kg)*	: <b>98,4</b>
Net weight (kg)*	: <b>82,4</b>
Dimensions in packaging H x W x D (mm)	: <b>1940 x 700 x 750</b>
Dimensions H x W x D(mm)	: <b>1825 x 680 x 700</b>
Color scheme	: <b>Black</b>

Energy efficiency rating	: <b>A+</b>
Acoustic emissions (dB(A))****	: <b>37</b>
Electrical power (W)***	: <b>70</b>
Electrical intensity (A)***	: <b>0.33</b>
Consumption per 24h (KWh) ****	: <b>0.35</b>
Annual energy consumption AEc* (kWh/year) ****	: <b>128</b>
Ambient temperature operating limit	: <b>0 - 35°C</b>

- ✓ Digital electronic controls
- ✓ Temperature display on indoor sidewall
- ✓ Double Hot/ Cold circuit > Automatic « Winter function »
- ✓ Temperature fault alarm icon
- ✓ Interior lining of dimpled aluminium
- ✓ Solid door
- ✓ Hygrometry ensured by the principle of thermodynamic pump
- ✓ 2 adjustable feet
- ✓ Lock
- ✓ Storage grid in the low part
- ✓ Inox Handle

Description	Reference	EAN Code
Single Solid beechwood universal shelf	AOHUI	3543290002783

\* Standard configuration

\*\* Traditional Bordeaux bottles

\*\*\* Calculated with an ambient temperature of 25°C

\*\*\*\* Consumption calculated with an ambient temperature of 25°C using an appliance with standard configuration

\*\*\*\*\* R600a gas. With a R134a gas (for US, CA, Korea, Taiwan): 38 db(A)